

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : Crystal Lacquer
Product code : C1

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive Coating

1.3. Supplier

GTECHNIQ LTD Bridge Business Park Upper Heyford Northampton, NN7 3FA - United Kingdom T +44 (0)1604 962 553 uk@gtechniq.com - www.gtechniq.com	GTECHNIQ NORTH AMERICA 4780 Hammond Industrial Drive Suite 100 Cumming GA 30041 T (855) 483-2401 infona@gtechniq.com - www.gtechniq.com
--	---

1.4. Emergency telephone number

Emergency number : +44 (0)1933 445 260
For Chemical Emergency Call 24hr / day, 7 days / week.

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquids Category 2	H225 Highly flammable liquid and vapor
Hazardous to the aquatic environment - Acute Hazard Category 3	H402 Harmful to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) : P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substances**

Not applicable

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS US classification
heptane	(CAS-No.) 142-82-5	1 – 10	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May be irritating to the respiratory system.
- Symptoms/effects after skin contact : May cause irritation to skin.
- Symptoms/effects after eye contact : May cause eye irritation.
- Symptoms/effects after ingestion : May cause irritation to the digestive tract.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : Containers may explode when heated.
- Reactivity in case of fire : Not known.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Precautionary measures fire : Eliminate all ignition sources if safe to do so. Keep container closed when not in use.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid breathing vapour or mist.

6.1.1. For non-emergency personnel

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Eliminate all ignition sources if safe to do so. Ventilate area.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Do not breathe fume, mist, spray, vapors.
- Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spillage.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).
- Other information : This material and its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Do not breathe fume, mist, spray, vapors. Provide good ventilation in process area to prevent formation of vapor. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wear suitable protective clothing, gloves and eye or face protection. Use only non-sparking tools. Ground/bond container and receiving equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use only non-sparking tools.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Sources of ignition, Direct sunlight. Keep container closed when not in use.
- Incompatible materials : Sources of ignition. Direct sunlight. Strong oxidizing agents.
- Heat-ignition : No flames, no sparks. Eliminate all sources of ignition.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Crystal Lacquer	
No additional information available	
heptane (142-82-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Heptane, isomers (n-Heptane)
ACGIH TWA (ppm)	400 ppm
ACGIH STEL (ppm)	500 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	Heptane (n-Heptane)
OSHA PEL (TWA) (mg/m³)	2000 mg/m³
OSHA PEL (TWA) (ppm)	500 ppm
Regulatory reference (US-OSHA)	OSHA

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure adequate ventilation. Use spark-/explosionproof appliances and lighting system.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. PPE compliant to the recommended EN/ISO or equivalent standards should be selected.

Hand protection:

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

In case of repeated or prolonged contact wear gloves

Eye protection:

Chemical goggles or safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask. Where exposure through inhalation may occur from handling or use, respiratory protection equipment is required. Exposure limits for airborne contaminants must not be exceeded.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: slight
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 82 °C
Flash point	: -3 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.95
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable at ambient temperature and under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Extremely high or low temperatures. Direct sunlight.

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

heptane (142-82-5)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: May be irritating to the respiratory system.
Symptoms/effects after skin contact	: May cause irritation to skin.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Crystal Lacquer

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Crystal Lacquer

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1993 Flammable liquids, n.o.s. (Silicone oligomer), 3, II
- UN-No.(DOT) : UN1993
- Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
Silicone oligomer
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : II - Medium Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- Emergency Response Guide (ERG) Number : 128
- Other information : No supplementary information available.

Transportation of Dangerous Goods

- Transport document description : UN1993 FLAMMABLE LIQUID, N.O.S. (Silicone oligomer), 3, II
- UN-No. (TDG) : UN1993
- Proper Shipping Name (Transportation of Dangerous Goods) : FLAMMABLE LIQUID, N.O.S.
- TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
- Packing group : II - Medium Danger

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan).
Explosive Limit and Limited Quantity Index	: 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L

Transport by sea

Transport document description (IMDG)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (Silicone oligomer), 3, II
UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 1 L

Air transport

Transport document description (IATA)	: UN 1993 Flammable liquid, n.o.s. (Silicone oligomer), 3, II
UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

Crystal Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.