

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Glass and Plexiglass Coating US
Product code : MGC

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive Coating

1.3. Supplier

GTECHNIQ LTD	GTECHNIQ NORTH AMERICA
Bridge Business Park	4780 Hammond Industrial Drive
Upper Heyford	Suite 100
Northampton, NN7 3FA - United Kingdom	Cumming GA 30041
T +44 (0)1604 962 553	T (855) 483-2401
uk@gtechniq.com - www.gtechniq.com	infona@gtechniq.com - www.gtechniq.com

1.4. Emergency telephone number

Emergency number : +44 (0)1933 445 260
For Chemical Emergency Call 24hr / day, 7 days / week.

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226 Flammable liquid and vapor
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 1	H318 Causes serious eye damage
Carcinogenicity Category 1A	H350 May cause cancer
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H318 - Causes serious eye damage
H350 - May cause cancer
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	(CAS-No.) 93685-81-5	12.5 - 20	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics		5 - 10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
sulphuric acid ... %	(CAS-No.) 7664-93-9	5 - 10	Met. Corr. 1, H290 Skin Corr. 1A, H314 Carc. 1A, H350 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- | | |
|---------------------------------------|---|
| First-aid measures general | : Call a physician immediately. Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Do not induce vomiting. Call a physician immediately. Call a poison center/doctor/physician if you feel unwell. |

4.2. Most important symptoms and effects (acute and delayed)

- | | |
|-------------------------------------|--|
| Symptoms/effects | : Suspected of causing cancer. |
| Symptoms/effects after inhalation | : Irritation to the respiratory tract. |
| Symptoms/effects after skin contact | : Causes skin irritation. |
| Symptoms/effects after eye contact | : Causes serious eye damage. |
| Symptoms/effects after ingestion | : May cause irritation to the digestive tract. |

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically. Call a doctor.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Specific hazards arising from the chemical

- | | |
|--|---|
| Fire hazard | : Flammable liquid and vapor. |
| Explosion hazard | : Explosion risk in case of fire. |
| Reactivity in case of fire | : Not known. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. Carbon monoxide. Carbon dioxide. hydrocarbons. |

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|--|
| Precautionary measures fire | : Exercise caution when fighting any chemical fire. |
| Firefighting instructions | : Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not attempt to take action without suitable protective equipment.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. In case of insufficient ventilation, wear suitable respiratory equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing fume, mist, spray, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area. Evacuate unnecessary personnel.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spillage.

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

Other information : This material and its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing fume, vapors, mist, spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place. Store in a closed container. Store locked up. Keep cool.

Incompatible materials : Strong acids. Strong bases. Strong oxidizing agents.

Heat-ignition : No flames, no sparks. Eliminate all sources of ignition.

Storage area : Store in a well-ventilated place.

Packaging materials : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glass and Plexiglass Coating US	
No additional information available	
Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated (93685-81-5)	
No additional information available	
sulphuric acid ... % (7664-93-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sulfuric acid
ACGIH TWA (mg/m³)	0.2 mg/m³
Remark (ACGIH)	Pulm func
Regulatory reference	ACGIH 2020

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA - OSHA - Occupational Exposure Limits

Local name	Sulfuric acid
OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. PPE compliant to the recommended EN/ISO or equivalent standards should be selected.

Materials for protective clothing:

Wear suitable coveralls to prevent exposure to the skin

Hand protection:

Protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask. Where exposure through inhalation may occur from handling or use, respiratory protection equipment is required. Exposure limits for airborne contaminants must not be exceeded.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: brown
Odor	: Solvent-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: 31 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 0.14 mbar
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.92 g/cm ³
Solubility	: Insoluble. Water: Solubility in water of component(s) of the mixture : • sulphuric acid ... %: 1000000 mg/l
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 200 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: 310.978 mm ² /s

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: 286.1 mPa-s
Explosion limits	: Lower explosive limit (LEL): 0.6 vol % Upper explosive limit (UEL): 7 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content	: ≤ 5 %
-------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

sulphuric acid ... % (7664-93-9)	
LD50 oral rat	2140 mg/kg body weight Animal: rat, 95% CL: 1540 - 2990
LC50 inhalation rat (mg/l)	0.375 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
ATE US (oral)	2140 mg/kg body weight
ATE US (dust, mist)	375 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

sulphuric acid ... % (7664-93-9)	
National Toxicology Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity	: Not classified
-----------------------	------------------

STOT-single exposure	: Not classified
----------------------	------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Aspiration hazard	: Not classified
Viscosity, kinematic	: 310.978 mm²/s

Symptoms/effects	: Suspected of causing cancer.
Symptoms/effects after inhalation	: Irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Causes serious eye damage.
Symptoms/effects after ingestion : May cause irritation to the digestive tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Before neutralisation, the product may represent a danger to aquatic organisms.

sulphuric acid ... % (7664-93-9)	
LC50 fish 1	> 16 mg/l
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
EC50 other aquatic organisms 1	> 100 mg/l waterflea
EC50 other aquatic organisms 2	> 100 mg/l
NOEC (chronic)	0.15 mg/l Test organisms (species): other: Tanytarsus dissimilis
NOEC chronic fish	0.31 mg/l Test organisms (species): Salvelinus fontinalis

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

sulphuric acid ... % (7664-93-9)	
Partition coefficient n-octanol/water (Log Pow)	-2.2

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III
UN-No.(DOT) : UN1993
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III

UN-No. (TDG) : UN1993

Proper Shipping Name (Transportation of Dangerous Goods) : FLAMMABLE LIQUID, N.O.S.

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group : III - Minor Danger

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan).
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

Transport by sea

Transport document description (IMDG)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III
UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 1993 Flammable liquid, n.o.s. (Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated), 3, III
UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated (93685-81-5)	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
sulphuric acid ... % (7664-93-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313 Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated (93685-81-5)	
Listed on the Canadian DSL (Domestic Substances List)	

Glass and Plexiglass Coating US

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

sulphuric acid ... % (7664-93-9)

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

Component	State or local regulations
sulphuric acid ... %(7664-93-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapor
H290	May be corrosive to metals
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H350	May cause cancer
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.